

ELITE PRIMER

100% Acrylic high-performance white primer



STATUS ELITE, 2 in 1 White Primer is a highest performing 100% acrylic, ecological, white primer, that delivers maximum hide and ensures superior priming. This innovative product integrates the best technologies to offer incomparable advantages in only one package. With a perfect adhesion to the substrate, the Stain-Blocking & High Hiding Formula is designed to stop toughest stains and to hides surface colored imperfections, together with the special mildew resistant recipe provide the best foundation primer before the finishing with other STATUS premium paints.



Advantages:

- Product environmentally friendly and solvent-free.
- Odorless.
- Does not contain ammonia.
- High penetration.
- Strong adhesion.
- Fast drying.
- Excellent coverage.
- Excellent workability.
- High performance.
- It prevents irregular absorption when applying the top coats. Ensure a perfect support for achieving the highest quality finishes.
- Can be colored in thousands shades.



TECHNICAL CHARACTERISTICS

Packaging:

Plastic containers
• 3 lt
• 9 lt

Color:

Available in white and in a numerous shades through STATUS coloring system.

Drying time:

- Touch dry 2-3 h
- Recoating 5-6 h

*Drying times refer to normal ambient conditions (25°C, 60% humidity). Drying times may differ in case of ambient temperature and humidity variations.

Dilution with water:

5-15 (% v.v.)

Application:

For exterior and interior use. Walls, ceilings, plaster, gypsum boards, masonry, brick, woodwork, etc.

Consumption:

14-18 m²/lt

Application tools:

Brush, roller, or airless gun.

Storage:

Store in tightly closed container for 36 months of the date of production only if it has not been thinned. Store in a cool and dry place.

V.O.C. class :

V.O.C. CLASS(g) Primers. V.O.C limit : 15 gr/lt.
Minimum thinning with water : 5 % v/v.
Maximum V.O.C. of product ready to use : 14,8 gr/lt.

FIELDS OF APPLICATION

Suitable for interior and exterior surfaces as walls and ceilings.

Suitable for plaster, gypsum boards, masonry, brick, woodwork etc.

SUBSTRATE PREPARATION

The surface must necessarily be clean, dry, sound and free from dust, mold, grease before applying. Remove all frayed, or peeling old paint. Where necessary grouting, use the STATUS 100% ACRYLIC PUTTY and after drying, rub with sandpaper and dust well. Where there are large cracks, use for grouting the ready to use Lightweight, White Stucco STATUS ONE COVER, with a single pass without rubbing. Never be applied to surfaces that may contain moisture. First make sure that the cause of the moisture stopped and that the surface is completely dry.

APPLICATION

Stir well the product inside the container before use, dilute appropriate and apply. After use close well the container to maintain the product in good condition for future use. It can be stored in a tightly closed container, without any problem for a long period provided that it hasn't been diluted. The application of the product on absorbent or very rough surfaces is made by spray. In this way we ensure penetration of the product throughout the surface, speed of application and low consumption. During application we should ensure that the product is absorbed and not simply deposited on the top of the surfaces forming a skin. After application any leftovers (ponds) must be removed. On newly plastered or concreted surfaces the paint application should be done only after 30-40 days.

APPLICATION TEMPERATURE

During the application temperatures should be at 5°-35°C and <80% RH. Do not start the application before rain. Ensure the surface is protected from direct solar radiation throughout the process. Adverse conditions during or immediately after application may affect the final properties of the product.

TOOL CLEANING

Immediately after use, drain excess paint thoroughly into the container and clean tools using warm soapy water. Do not dispose of washing waste water into the aquifer groundwater.

COMMENTS

More information regarding the reasons why this product was given the EU Ecolabel can be found on the EU website:

<http://ec.europa.eu/environment/ecolabel/>

PRECAUTIONS

For information on the safe use, storage and disposal of the product read the information on the label and in the most recent Product Safety Data Sheet. The Product Safety Data Sheet is available at the professionals' request. Remaining paint should not be disposed of with household waste. You should seek advice from local authorities regarding the disposal and collection of waste.

[Poisons Information Call Center 210 77.93.777](http://210.77.93.777)

Technical characteristic	Units	Standard	Value
Viscosity	cP	EN ISO 2555	6400 – 8000
Density	g/ml	EN ISO 2811-1	1.29 ± 0.03
pH		ISO 976	8.0 – 9.0
Gloss (60° C)		ISO 2813	≤3
Dilution	%		5-15
Recoating time	h		5 – 6
Drying time	h		2 - 3

*Note: The measurements were taken in laboratory environment under a temperature of +23°C, Relative humidity 50% and without ventilation. It is possible for them to vary depending on the conditions prevailing at the worksite, such as temperature, humidity, ventilation, absorbability of the substrate.

The technical information and instructions contained in the present brochure and referring to the application and end use of Thrakon products are based on the up to now know-how and experience of the Company with regards to the products and are provided in good faith as long as such products are stored, used and applied as per Thrakon recommendations. Due to the inability, on our part, to directly inspect the conditions prevailing at the worksite as well as the application procedures of the product, the Company does not provide any guarantee with regards to the adequacy of its products for specific purpose while the Company shall not bear any legal responsibility based on the information stated in the present brochure or any other written, oral, or otherwise provided recommendations and instructions. The users of the products are advised to perform a limited surface testing of the products adequacy for the eventual application and use intentions. Thrakon reserves the right to modify the features of its products without prior notification. All orders shall be approved only following acceptance of the above and under the eventual Commercial Policy terms of the Company. The issuance of the present brochure voids any prior version.

Version C: 24/07/2024