

# LUXURIOUS

## Premium ecological velvet emulsion paint



STATUS LUXURIOUS is a premium velvet, ecological, high quality emulsion paint ideal for interior use. It offers unrivalled performance on all levels. It is odorless and absolutely user and environment-friendly. It is easy to apply, it spreads fabulously and it has excellent hiding power and high efficiency. It is especially recommended for children's rooms, nurseries and hospitals because it is odorless, easy to clean, it is resistant to frequent washing and minor impacts (CLASS 1). It offers a rich, velvety surface, giving the pleasure of freshly painted home for a long time. It does not contain ammonia, or other hazardous substances such as heavy metals, aromatic hydrocarbons, alkyl phenolic compounds or free formaldehyde.



### Advantages:

- Environment-friendly and solvent-free.
- It has ECO labeling.
- Odorless.
- Does not contain ammonia and other harmful substances.
- Provides excellent surface perspirations.
- Excellent wash resistance, Class 1.
- Excellent coverage.
- Highly resistant to wear and aging.
- Suitable for use in kindergartens, children's rooms, schools, hospitals.
- Excellent workability.



## TECHNICAL CHARACTERISTICS



### Packaging:

Plastic containers  
• 0,75 lt  
• 3 lt  
• 9 lt

### Color:

Available in white.  
Tinted in pale shades  
using the STATUS  
emulsion colorants.



### Fan decks:

Color system STATUS  
emulsion colorants.



### Drying time:

- Touch dry  
1 - 2 h
- Recoating  
2 - 3 h

\*Drying times refer to normal ambient conditions (25°C, 60% humidity). Drying times may differ in case of ambient temperature and humidity variations.



### Dilution with water:

10 - 15 (% v.v.)



### Application:

For interior use.  
Walls, plaster,  
ceilings,  
plasterboards,  
spatula coated  
surfaces, etc.



### Consumption:

15 - 18 m<sup>2</sup>/lt



### Application tools:

Brush, roller, or airless gun.



### Storage:

Store the original, sealed containers in dry place at temperatures between +5°C and +35°C for 24 months from production date.



### V.O.C. class :

(a) Interior walls and ceilings (gloss < 25 at 60°) (W.B) V.O.C limit: 10 gr/lt  
Minimum thinning with water: 10% v/v  
Maximum V.O.C limit of ready to use product: 7.7 gr/lt

## FIELDS OF APPLICATION

Suitable for interiors on all ordinary surfaces such as walls, plaster, ceilings, plasterboards, spatula coated surfaces, etc.

Highly recommended for children's rooms, kindergartens and hospitals.

Use on wooden surfaces after adequate preparation.

## SUBSTRATE PREPARATION

Before use, ensure that the surface is clean, dry, robust and free from dust, mold and grease. Remove damaged, or peeling old paint. Where puttying is required, use the STATUS 100% ACRYLIC STUCCO and after drying, sand the surface down and clean the dust well. If there are large cracks, use the ready-to-use light white Stucco, STATUS ONE COVER, to fill the cracks applying just one coat without sanding. On new surfaces, first apply one coat of STATUS ACRYLIC PRIMER, STATUS AQUADUR or GLX 292 FLEX PRIM. For surfaces covered in fresh plaster or cement, allow the surfaces to dry thoroughly for at least one month before painting.

## APPLICATION

Mix well before use, dilute properly and apply 1-2 coats of paint. Allow at least 2-3 hours before applying the second coat. Close the container tightly after use to keep the paint in good condition for future use. You can store undiluted paint in a tightly sealed container for extended periods of time without affecting the quality of the product. Allow 20-30 days before washing painted surfaces and 30-40 days before washing freshly painted new plaster or concrete surfaces. The painted surfaces can be cleaned using a soft sponge with water. If stains persist, use a mild, colorless detergent.

## APPLICATION TEMPERATURE

During the application temperatures should be at 5°-35°C and <80% RH. Do not start the application before rain. Ensure the surface is protected from direct solar radiation throughout the process. Adverse conditions during or immediately after application may affect the final properties of the product.

## TOOL CLEANING

Immediately after use, drain excess paint thoroughly into the container and clean tools using warm soapy water. Do not dispose of washing waste water into the aquifer groundwater.

## COMMENTS

More information regarding the reasons why this product was given the EU Ecolabel can be found on the EU website:

<http://ec.europa.eu/environment/ecolabel/>

## PRECAUTIONS

For information on the safe use, storage and disposal of the product read the information on the label and in the most recent Product Safety Data Sheet. The Product Safety Data Sheet is available at the professionals' request. Remaining paint should not be disposed of with household waste. You should seek advice from local authorities regarding the disposal and collection of waste.

[Poisons Information Call Center 210 77.93.777](tel:2107793777)

Technical characteristics	Units	Standard	Value
Vsicosity	cP	EN ISO 2555	8000 – 12000
Density	g/ml	EN ISO 2811-1	1.34 ± 0.03
pH		ISO 976	8.0 – 9.0
Gloss (60° C)	%	EN ISO 2813	≤3
Dilution	%		10-15
Recoating time	h		2 – 3
Drying time	h		1 – 2
Washing-scrubbing resistance		EN ISO 11998	Class 1

\*Note: The measurements were taken in laboratory environment under a temperature of +23°C, Relative humidity 50% and without ventilation. It is possible for them to vary depending on the conditions prevailing at the worksite, such as temperature, humidity, ventilation, absorbability of the substrate.

The technical information and instructions contained in the present brochure and referring to the application and end use of Thrakon products are based on the up to now know-how and experience of the Company with regards to the products and are provided in good faith as long as such products are stored, used and applied as per Thrakon recommendations. Due to the inability, on our part, to directly inspect the conditions prevailing at the worksite as well as the application procedures of the product, the Company does not provide any guarantee with regards to the adequacy of its products for specific purpose while the Company shall not bear any legal responsibility based on the information stated in the present brochure or any other written, oral, or otherwise provided recommendations and instructions. The users of the products are advised to perform a limited surface testing of the products adequacy for the eventual application and use intentions. Thrakon reserves the right to modify the features of its products without prior notification. All orders shall be approved only following acceptance of the above and under the eventual Commercial Policy terms of the Company. The issuance of the present brochure voids any prior version.

Version E: 08/10/2024