

# STATUS AQUADUR

## Micronized acrylic water-based primer



STATUS AQUADUR is a transparent, waterproof, micronized acrylic water-based primer. It is odorless and friendly for the user and the environment. Its high penetration ability makes it ideal for the preparation of any new or old porous surfaces such as plaster, brick, concrete, plastered walls etc. It is also an ideal solution for surfaces coated with glue, lime or cheap old paints. Deeply impregnates the surfaces while allowing them to breathe. It is the ideal preparation before painting with emulsion or acrylic paints, acrylic paints, relief, cement-paint or insulating materials. It stabilizes the substrates it impregnates and ensures a strong base for the adhesion of topcoats, providing higher yields, improved coverage and significantly greater durability.



### Advantages:

- High penetration.
- Strong adhesion.
- Stabilizes the loose surfaces.
- Reduces the absorption of porous surfaces.
- Fast drying.
- Excellent coverage.
- Great workability.
- High performance.



## TECHNICAL CHARACTERISTICS

### Packaging:

Plastic containers  
• 1 lt  
• 5 lt

### Color:

Whitish in packaging.  
Becomes transparent after application.

### Drying time:

- Touch dry  
1 h
- Recoating  
4 – 5 h

\*Drying times refer to normal ambient conditions (25°C, 60% humidity). Drying times may differ in case of ambient temperature and humidity variations.

### Consumption:

15-20 m<sup>2</sup>/lt

### Application:

For interior and exterior use. Exposed concrete, plaster, plasterboards, stucco surfaces, brick, etc.

### Dilution with water:

Up to 100 (% v.v.)

### Storage:

Store the original, sealed containers in dry environment at temperatures between +5°C and +35°C for 24 months from production date.

### V.O.C. class :

A/c Coatings and exterior walls of mineral substrate, TYPE Y, V.O.C limit: 30 gr/lt. Maximum V.O.C of product ready to use: 29 gr/lt.

### Application tools:

Brush, roller, or airless gun.

## FIELDS OF APPLICATION

Suitable for the preparation of new surfaces, such as exposed concrete, plaster, plasterboard, stucco surfaces, brick etc. Paint with acrylic or emulsion paints.

Suitable for stabilizing surfaces painted with watercolors (glue) or lime.

Suitable for the reduction of the absorbency of porous surfaces and the preparation before painting with insulating materials.

## SUBSTRATE PREPARATION

Before applying, ensure that the surface is clean, dry, robust and free from dust, mold and grease. Remove all frayed or peeling old paint. Where putty is required, use the STATUS 100% ACRYLIC PUTTY and after drying, sand the surface and clean the dust thoroughly. If there are large cracks, use the ready-to-use white stucco STATUS ONE COVER, fill the cracks applying just one coat without sanding. Never apply to surfaces that may contain moisture. First make sure that the cause of the moisture has stopped and that the surface is completely dry.

## APPLICATION

Mix well before use, dilute properly and apply 1 coat of paint. Then close the container tightly after use to keep the paint in good condition for future use. You can store the paint in a tightly sealed container for extended periods of time without affecting the quality of the product. If there is a need to apply a second layer, apply at least 4-5 hours after the first one. The application of the product on very rough surfaces should be done by spraying. When applying you should make sure that the product is absorbed and not just deposited on the substrate forming a skin. After application you must remove any leftovers (ponds). On new plaster or concrete application must be done after 30-40 days.

## APPLICATION TEMPERATURE

During the application temperatures should be at 5°-35°C and <80% RH. Do not start the application before rain. Ensure the surface is protected from direct solar radiation throughout the process. Adverse conditions during or immediately after application may affect the final properties of the product.

## TOOL CLEANING

Immediately after use, drain excess paint thoroughly into the container and clean tools using warm soapy water. Do not dispose of washing waste water into the aquifer groundwater.

## PRECAUTIONS

For information on the safe use, storage and disposal of the product read the information on the label and in the most recent Product Safety Data Sheet. The Product Safety Data Sheet is available at the professionals' request. Remaining paint should not be disposed of with household waste. You should seek advice from local authorities regarding the disposal and collection of waste.

[Poisons Information Call Center 210 77.93.777](tel:2107793777)

Technical characteristics	Units	Standard	Value
Viscosity	sec	ASTM D 5125, ISO 2431	40 - 70
Density	g/ml	EN ISO 2811-1	1.01 ± 0.03
pH		ISO 976	8.0 – 9.0
Dilution	%		Up to 100
Recoating time	h		4 – 5
Drying time	h		1

\*Note: The measurements were taken in laboratory environment under a temperature of +23°C, Relative humidity 50% and without ventilation. It is possible for them to vary depending on the conditions prevailing at the worksite, such as temperature, humidity, ventilation, absorbability of the substrate.

The technical information and instructions contained in the present brochure and referring to the application and end use of Thrakon products are based on the up to now know-how and experience of the Company with regards to the products and are provided in good faith as long as such products are stored, used and applied as per Thrakon recommendations. Due to the inability, on our part, to directly inspect the conditions prevailing at the worksite as well as the application procedures of the product, the Company does not provide any guarantee with regards to the adequacy of its products for specific purpose while the Company shall not bear any legal responsibility based on the information stated in the present brochure or any other written, oral, or otherwise provided recommendations and instructions. The users of the products are advised to perform a limited surface testing of the products adequacy for the eventual application and use intentions. Thrakon reserves the right to modify the features of its products without prior notification. All orders shall be approved only following acceptance of the above and under the eventual Commercial Policy terms of the Company. The issuance of the present brochure voids any prior version.

Version B: 21/11/2024