

# STATUS DUROMETAL HARDENER

## Alkyd paint hardener



STATUS DUROMETAL HARDENER is an additional hardener for alkyd enamel paints. It provides the paint film with increased hardness withing less time. Enhances resistance to impacts and friction. Guarantees faster drying and higher tolerance to weather changes and solvents. This product helps preserve the surface's gloss and color integrity, even when exposed to the harshest weather conditions.



**Advantages:**

- Exceptional resistance to impact and fiction.
- Faster drying.
- Increased hardness.
- Protects gloss and shade.
- Higher tolerance to weather changes and solvents.



### TECHNICAL CHARACTERISTICS



**Packaging:**

Metallic container  
• 750 ml



**Color:**

Transparent.



**Drying:**

- To the touch  
2 - 3 h
- Recoating  
16 h

\*Drying times refer to normal ambient conditions (25°C, 60% humidity). Drying times may differ in case of ambient temperature and humidity variations.



**Application:**

For exterior and interior use. Suitable for alkyd-based enamel paints.



**Consumption:**

Up to 20% v/v with all enamel paints.



**Application tools:**

Brush, roller or airless gun.



**Storage:**

After application close the container tightly and store in places with low humidity.

## FIELDS OF APPLICATION

Suitable for alkyd-based enamel paints.

## APPLICATION

The product does not require any dilution during application. Use up to 20% v/v because any amount larger than the specified shall make the film hard and fragile. Mix well and apply. After the addition of the hardener into the paint, use the mixture within 2 hours otherwise the product hardens inside the container. Close the used container tightly and store in places with low humidity.

## APPLICATION TEMPERATURE

During the application temperatures should be at 5°-35°C and <80% RH. Do not start the application before rain. Ensure the surface is protected from direct solar radiation throughout the process. Adverse conditions during or immediately after application may affect the final properties of the product.

## TOOL CLEANING

Throughout the application, keep the tools “wet” inside the container with the paint. Remove all the paint from the tools and empty it into the container. Immediately after use, clean the brush, or roll with WHITE SPIRIT and then with hot water and detergent. Do not empty washings into the groundwater.

## PRECAUTIONS

For information on the safe use, storage and disposal of the product read the information on the label and in the most recent Product Safety Data Sheet. The Product Safety Data Sheet is available at the professionals’ request. Remaining paint should not be disposed of with household waste. You should seek advice from local authorities regarding the disposal and collection of waste.

[Poisons Information Call Center 210 77.93.777](tel:2107793777)

Technical characteristics	Units	Standard	Value
Viscosity	sec	ASTM D 5125, ISO 2431	10 – 12
Density	g/ml	EN ISO 2811-1	0.94 ± 0.03

\*Note: The measurements were taken in laboratory environment under a temperature of +23°C, Relative humidity 50% and without ventilation. It is possible for them to vary depending on the conditions prevailing at the worksite, such as temperature, humidity, ventilation, absorbability of the substrate.

The technical information and instructions contained in the present brochure and referring to the application and end use of Thrakon products are based on the up to now know-how and experience of the Company with regards to the products and are provided in good faith as long as such products are stored, used and applied as per Thrakon recommendations. Due to the inability, on our part, to directly inspect the conditions prevailing at the worksite as well as the application procedures of the product, the Company does not provide any guarantee with regards to the adequacy of its products for specific purpose while the Company shall not bear any legal responsibility based on the information stated in the present brochure or any other written, oral, or otherwise provided recommendations and instructions. The users of the products are advised to perform a limited surface testing of the products adequacy for the eventual application and use intentions. Thrakon reserves the right to modify the features of its products without prior notification. All orders shall be approved only following acceptance of the above and under the eventual Commercial Policy terms of the Company. The issuance of the present brochure voids any prior version.

Version B: 26/07/2024