

STATUS DUR

Waterproofing solvent-based acrylic primer

STATUS DUR is a clear, waterproof, acrylic solvent-based primer. Its high penetration makes it ideal for the preparation of any new or old porous surface such as plaster, bricks, concrete, spatula coated walls etc. It is also the best solution for surfaces painted with adhesive, lime whitewash, or poor-quality old paints. Impregnates and waterproofs the surfaces, while allowing them to breathe. It is the best preparation before painting with emulsion, acrylic, relief, cement surface paints or insulating materials. Stabilizes the impregnated surface and ensures strong adhesion base for the topcoat, providing higher performance, improved coverage and significantly greater durability. Replaces traditional linseed oil, dries faster without leaving a yellow tint.



Πλεονεκτήματα:

- High penetration.
- Strong adhesion.
- Stabilizes loose surfaces.
- Reduced absorption of porous surfaces.
- Fast drying.
- Excellent coverage.
- Highly workable.
- Great performance.
- Replaces traditional linoleum.
- No yellow tint.



TECHNICAL CHARACTERISTICS

Packaging:

- Tin cans
- 1 lt
- 5 lt
- 15 lt

Color:

Transparent.

Application:

For interior and exterior use. Concrete, plaster, plasterboards, spatula coated surfaces, bricks etc.

Drying time:

- Touch dry 1 h
- Recoating 2 - 3 h

*Drying times refer to normal ambient conditions (25°C, 60% humidity). Drying times may differ in case of ambient temperature and humidity variations.

Dilution with white spirit:

- 100 (% v.v.) for walls
- 25 (% v.v.) for rooftops

Consumption:

- 14-16 m²/lt when applying to walls.
- 8-10 m²/lt when applying to rooftops.

Storage:

Store the original, sealed containers in dry place at temperatures between +5°C and +35°C for 36 months from production date.

V.O.C. class :

A/h Binding primers (W.B) V.O.C limit: 750 gr/lt.
Maximum dilution of 100% v/v
Maximum V.O.C of product ready to use: 740 gr/lt.

FIELDS OF APPLICATION

Suitable for the preparation of new surfaces, such as fair-faced concrete, plaster, plasterboards, spatula coated surfaces, bricks etc. for painting with emulsion or acrylic paints.

Stabilization of surfaces painted with watercolors (adhesive) or whitewash.

Reduction of the absorption of porous surfaces.

Preparation before painting with insulating materials.

SUBSTRATE PREPARATION

Before applying, ensure that the surface is clean, dry, robust and free from dust, mold and grease. Remove damaged, or peeling old paint. Where putting is required, use the STATUS 100% ACRYLIC PUTTY and after drying, sand the surface and clean the dust thoroughly. If there are large cracks, use the ready-to-use light white stucco STATUS ONE COVER to fill the cracks applying just one coat without sanding. Never apply to surfaces that may contain moisture. First make sure that the cause of the moisture has stopped and that the surface is completely dry.

APPLICATION

Mix well before use, dilute properly and apply. Allow at least 2-3 hours before applying the second coat if needed. Close the container tightly after use to keep the paint in good condition for future use. You can store undiluted paint in a tightly sealed container for extended periods of time without affecting the quality of the product. The material is sprayed onto absorbent or very rough surfaces. This ensures uniform penetration, fast application and cost efficiency. When applying, ensure that the primer is absorbed and does not simply sit on the surfaces to form a skin. After application, residues (pools) must be removed. On new plaster or concrete, the primer should be applied after a period of 30-40 days.

APPLICATION TEMPERATURE

During the application temperatures should be at 5°-35°C and <80% RH. Do not start the application before rain. Ensure the surface is protected from direct solar radiation throughout the process. Adverse conditions during or immediately after application may affect the final properties of the product.

TOOL CLEANING

Clean all tools with White Spirit immediately after use and then with hot water and detergent. Do not dispose of washing waste water into the aquifer groundwater.

PRECAUTIONS

For information on the safe use, storage and disposal of the product read the information on the label and in the most recent Product Safety Data Sheet. The Product Safety Data Sheet is available at the professionals' request. Remaining paint should not be disposed of with household waste. You should seek advice from local authorities regarding the disposal and collection of waste.

[Poisons Information Call Center 210 77.93.777](tel:2107793777)

Technical characteristics		Units	Standard	Value
Viscosity		sec	ASTM D 5125, EN ISO 2811-1	13 - 16
Density		g/ml	EN ISO 2811-1	0.8 ± 0.03
Dilution	Application on walls	%		≤100%
	Application on rooftops			≤25%

*Note: The measurements were taken in laboratory environment under a temperature of +23°C, Relative humidity 50% and without ventilation. It is possible for them to vary depending on the conditions prevailing at the worksite, such as temperature, humidity, ventilation, absorbability of the substrate.

The technical information and instructions contained in the present brochure and referring to the application and end use of Thrakon products are based on the up to now know-how and experience of the Company with regards to the products and are provided in good faith as long as such products are stored, used and applied as per Thrakon recommendations. Due to the inability, on our part, to directly inspect the conditions prevailing at the worksite as well as the application procedures of the product, the Company does not provide any guarantee with regards to the adequacy of its products for specific purpose while the Company shall not bear any legal responsibility based on the information stated in the present brochure or any other written, oral, or otherwise provided recommendations and instructions. The users of the products are advised to perform a limited surface testing of the products adequacy for the eventual application and use intentions. Thrakon reserves the right to modify the features of its products without prior notification. All orders shall be approved only following acceptance of the above and under the eventual Commercial Policy terms of the Company. The issuance of the present brochure voids any prior version.

Version B: 24/11/2024