

STATUS EMULSION PAINT

Premium quality, mat emulsion paint



STATUS EMULSION PAINT is a premium high-quality emulsion paint ideal for interior walls. It is odorless and completely friendly for the user and the environment. It is easy to apply, it spreads superbly and it has excellent hiding power and high efficiency. It has excellent levelling properties providing a flawless, uniform and flat surface with excellent resistance to frequent washing (CLASS 1) maintaining the beautiful appearance for very long.

Advantages:

- Odorless.
- Product environmentally friendly and solvent-free..
- Does not contain ammonia.
- Excellent breathability of surfaces.
- Excellent resistance to sunlight.
- Resistant to washing.
- High resistance to weathering and ageing.
- Suitable for painting nurseries, children's rooms, schools, hospitals.
- Excellent workability.
- Excellent hiding power.
- Wet scrub resistance (CLASS 1)



TECHNICAL CHARACTERISTICS



Packaging:

- Plastic containers
- White: 0.75 lt, 3 lt, 10 lt
- Base P, D, TR: 1lt, 3 lt, 10 lt



Color:

Available in white and thousand more shades through the STATUS tinting system



Drying time:

- Touch dry 1 - 2 h
- Recoating 2 - 3 h

*Drying times refer to normal ambient conditions (25°C, 60% humidity). Drying times may differ in case of ambient temperature and humidity variations.



Dilution with water:

5-10(% v.v.)



Application:

For interior use. Walls, plasters, bathrooms, ceilings, store rooms, etc.



Consumption:

15-18 m²/lt



Application tools:

Brush, roller, or airless gun.



Storage:

Store in a tightly closed container in a cool and dry place at for 24 months of the date of productions only if has not been thinned.



V.O.C. class :

A/a. Interior matt walls and ceilings (gloss < 25 at 60°) (W.B) V.O.C limit: 30 gr/lt
Maximum V.O.C limit of ready to use product: 29 gr/lt

FIELDS OF APPLICATION

Suitable for indoor application in all usual building surfaces such as walls, plaster, ceilings, putties, etc. Application is made only after appropriate preparation on wood surfaces.

SUBSTRATE PREPARATION

The surface must necessarily be clean, dry, sound and free from dust, mold, grease before applying. Remove all frayed, or peeling old paint. Where necessary grouting, use the STATUS 100% ACRYLIC PUTTY and after drying, rub with sandpaper and dust well. Where there are large cracks, use the ready-to-use light-weight, white putty STATUS ONE COVER, with a single pass without rubbing. New surfaces, must be primed with STATUS ACRYLIC PRIMER, STATUS AQUADUR or GLX 292 FLEX PRIM. If it is fresh plaster or cement, let it dry absolutely thoroughly for at least one month before painting. On gypsum boards or for repainting water painted surfaces (with lime or glue) or soiled surfaces (nicotine, soot from heaters, soot, fumes, coffee, juice, graffiti, inks, markers, mildew, mold, moisture, oil, etc.), prime first with STATUS DUR

APPLICATION

Stir well the contents of the container before use, dilute properly and apply 1-2 coats of paint. Apply the second layer at least 2-3 hours after the first. After use close well the container to maintain the product in good condition for future use. It can be stored in a tightly closed container, without any problem for a long period provided that it hasn't been diluted with water. The painted surfaces is recommended not to be washed until 20-30 days have passed after the paint application. On newly plastered or concreted surfaces the paint application can be done only after 30-40 days. STATUS bases are used exclusively for the production of shades through the STATUS tinting system and should not be applied without the addition of special STATUS pigments. Very dark colors in matte shades that are subject to frequent washing are not recommended.

TOOL CLEANING

Immediately after use, drain excess paint thoroughly into the container and clean tools using warm soapy water. Do not dispose of washing waste water into the aquifer groundwater.

PRECAUTIONS

For information on the safe use, storage and disposal of the product read the information on the label and in the most recent Product Safety Data Sheet. The Product Safety Data Sheet is available at the professionals' request. Remaining paint should not be disposed of with household waste. You should seek advice from local authorities regarding the disposal and collection of waste.

[Poisons Information Call Center 210 77.93.777](tel:2107793777)

APPLICATION TEMPERATURE

During the application temperatures should be at 5°-35°C and <80% RH. Do not start the application before rain. Ensure the surface is protected from direct solar radiation throughout the process. Adverse conditions during or immediately after application may affect the final properties of the product.

Technical characteristics		Units	Standard	Value
Density	White and bases P, P(K), D Bases Brick, Ochre			1.42 ± 0.05
	Basic Yellow, Red, Black, Blue, Green	g/ml	EN ISO 2811.01-02	1.32 ± 0.05
	Base TR			1.52 ± 0.05
Viscosity		cP	Brookfield	10,000 – 20,000
pH			ISO 976-96	8.0 – 8.7
Gloss (60°)		%	EN ISO 2813-99	< 4
Tolerance to washing-scrubbing		Class	EN ISO 11998-02	1
Accelerated ageing through UV radiation (1000h)		°C	ISO 11507-97	There is no film alteration
Dilution with water		% v/v		5-10

*Note: The measurements were taken in laboratory environment under a temperature of +23°C, Relative humidity 50% and without ventilation. It is possible for them to vary depending on the conditions prevailing at the worksite, such as temperature, humidity, ventilation, absorbability of the substrate.

The technical information and instructions contained in the present brochure and referring to the application and end use of Thrakon products are based on the up to now know-how and experience of the Company with regards to the products and are provided in good faith as long as such products are stored, used and applied as per Thrakon recommendations. Due to the inability, on our part, to directly inspect the conditions prevailing at the worksite as well as the application procedures of the product, the Company does not provide any guarantee with regards to the adequacy of its products for specific purpose while the Company shall not bear any legal responsibility based on the information stated in the present brochure or any other written, oral, or otherwise provided recommendations and instructions. The users of the products are advised to perform a limited surface testing of the products adequacy for the eventual application and use intentions. Thrakon reserves the right to modify the features of its products without prior notification. All orders shall be approved only following acceptance of the above and under the eventual Commercial Policy terms of the Company. The issuance of the present brochure voids any prior version.

Version D: 22/07/2024