

# STATUS KITCHEN & BATH

## Antimould high quality emulsion paint

STATUS KITCHEN & BATH is a top-quality emulsion paint ideal for application on indoor surfaces with high moisture and vapour condensation, such as kitchens, bathrooms, ceilings, storerooms, etc. The special fungicide substances contained in the product prevent the growth of mold and bacteria, thus constituting an ideal solution for places such as pharmaceutical industries, food industries, operating theatres and accommodation facilities. It is odorless, ammonia-free and absolutely user and environmentally friendly. Easily applied and perfectly spread, it covers everything and is highly effective. The result is a perfectly matt surface that shows tolerance to frequent washing with detergents or disinfectants and maintains its beautiful appearance for a long time.

### Advantages:

- Environment-friendly and solvent-free.
- High protection against mold and fungi.
- Odorless.
- Ammonia-free.
- Resistant to washing.
- Perfect coverage.
- Resistance to detergents and disinfectants.
- Suitable for application in pharmaceutical industries, food industries, operating theatres and accommodation facilities.
- Excellent spreading.
- Excellent workability.
- High performance.



## TECHNICAL CHARACTERISTICS



### Packaging:

- Plastic containers
- 0.75 lt
- 3 lt
- 10 lt



### Color:

Available in white.



### Drying time:

- Touch dry  
1 - 2 h
- Recoating  
2 - 3 h

\*Drying times refer to normal ambient conditions (25°C, 60% humidity). Drying times may differ in case of ambient temperature and humidity variations.



### Dilution with water:

5-10(% v.v.)



### Application:

For interior use. Kitchens, bathrooms, ceilings, storerooms, etc.



### Consumption:

12 - 14 m<sup>2</sup>/lt



### Application tools:

Brush, roller, or airless gun.



### Storage:

Store in a tightly closed container in a cool and dry place at for 24 months of the date of productions only if has not been thinned.



### V.O.C. class :

A/a. Interior matt walls and ceilings (gloss < 25 at 60°) (W.B) V.O.C limit: 30 gr/lt  
Maximum V.O.C limit of ready to use product: 29 gr/lt

## FIELDS OF APPLICATION

Suitable for interiors on all ordinary surfaces such as walls, plaster, ceilings, plasterboards, spatula coated surfaces, etc.

Highly recommended for children's rooms, kindergartens and hospitals.

Use on wooden surfaces after adequate preparation.

## SUBSTRATE PREPARATION

The surface should necessarily be clean, dry, rigid and free from dust, mold and oil before application. Remove all detached or peeled old paints. If stucco is required, use STATUS 100% ACRYLIC STUCCO and after it dries, sandpaper and clean the dust well. In big cracks use the light, white ready for use STATUS ONE COVER acrylic putty. Apply only one layer without sanding. New surfaces should be primed with STATUS ACRYLIC PRIMER, STATUS AQUADUR or GLX 292 FLEX PRIM. For surfaces covered in fresh plaster or cement, allow the surfaces dry thoroughly for at least 1 month before painting. In gypsum boards and in case of surfaces recoated with water paints (with lime or adhesive) or stained surfaces (nicotine, smog from radiators, smut, exhaust fumes, coffee, juice, graffiti, ink, markers, fungi, mold, humidity, oil, etc.), first apply STATUS DUR primer.

## APPLICATION

Mix well the content of the container before use, dilute properly and apply 1-2 layers of paint. Apply the second layer at least 2-3 hours after the first. After application, close the container tightly to maintain in good condition for future use. It can be stored in a tightly closed container for a long time as long as it has not been diluted. Painted surfaces should not be washed before 20-30 days have passed after painting. In new surfaces from plaster or concrete, the paint should be applied after 30-40 days.

STATUS bases are exclusively used for the production of shades with the help of the STATUS coloring system and should not be applied without adding the special STATUS pigments. Very dark shades of matt paints that are frequently washed are not recommended.

## TOOL CLEANING

Immediately after use, drain excess paint thoroughly into the container and clean tools using warm soapy water. Do not dispose of washing waste water into the aquifer groundwater.

## PRECAUTIONS

For information on the safe use, storage and disposal of the product read the information on the label and in the most recent Product Safety Data Sheet. The Product Safety Data Sheet is available at the professionals' request. Remaining paint should not be disposed of with household waste. You should seek advice from local authorities regarding the disposal and collection of waste.

[Poisons Information Call Center 210 77.93.777](tel:2107793777)

## APPLICATION TEMPERATURE

During the application temperatures should be at 5°-35°C and <80% RH. Do not start the application before rain. Ensure the surface is protected from direct solar radiation throughout the process. Adverse conditions during or immediately after application may affect the final properties of the product.

Technical characteristics	Units	Standard	Value
Viscosity	cP	EN ISO 2555	10400 – 13600
Density	g/ml	EN ISO 2811-1	1.50 ± 0.03
pH		ISO 976	8.0 – 9.0
Gloss (60° C)	%	ISO 2813	≤3
Dilution	%		5 - 10
Recoating time	h		2 – 3
Drying time	h		1 - 2
Tolerance to rubbing-washing		EN ISO 11998	Class 2

\*Note: The measurements were taken in laboratory environment under a temperature of +23°C, Relative humidity 50% and without ventilation. It is possible for them to vary depending on the conditions prevailing at the worksite, such as temperature, humidity, ventilation, absorbability of the substrate.

The technical information and instructions contained in the present brochure and referring to the application and end use of Thrakon products are based on the up to now know-how and experience of the Company with regards to the products and are provided in good faith as long as such products are stored, used and applied as per Thrakon recommendations. Due to the inability, on our part, to directly inspect the conditions prevailing at the worksite as well as the application procedures of the product, the Company does not provide any guarantee with regards to the adequacy of its products for specific purpose while the Company shall not bear any legal responsibility based on the information stated in the present brochure or any other written, oral, or otherwise provided recommendations and instructions. The users of the products are advised to perform a limited surface testing of the products adequacy for the eventual application and use intentions. Thrakon reserves the right to modify the features of its products without prior notification. All orders shall be approved only following acceptance of the above and under the eventual Commercial Policy terms of the Company. The issuance of the present brochure voids any prior version.

Version D: 19/07/2024