

# STATUS RUST PRIMER

## Anticorrosive primer

STATUS RUST PRIMER is a fast-drying primer with excellent corrosion resistance and high strength. It is suitable for metallic surfaces such as railings, agricultural machinery, chassis, etc, providing effective protection against corrosion, even under adverse weather conditions. It stands out because it is applied gently, it spreads wonderfully and ensures the top coating a very strong adhesion to the metallic surface and provides an excellent final result. It has high spreading rate and excellent hiding power.



### Advantages:

- Excellent corrosion protection even under harsh weather conditions.
- Fast drying.
- High adhesion.
- Excellent leveling and workability.
- Excellent hiding power.
- High spreading rate.



## TECHNICAL CHARACTERISTICS

### Packaging:

- Metallic containers
- 0.375 lt
- 0.75 lt
- 2.5 lt

### Color:

Available in Grey and terracotta.



### Drying:

- Touch dry 5-6 h
- Recoating 12 h

\*Drying times refer to normal ambient conditions (25°C, 60% humidity). Drying times may differ in case of ambient temperature and humidity variations.

### Dilution:

- with white spirit or turpentine for application by brush or roller: 5-7 (% v.v.)
- with LS-703: 7-10 (% v.v.)

### Application:

For exterior and interior use. Suitable for rails, farming equipment, car frames, etc.

### Consumption:

13-15 m<sup>2</sup>/lt

### Application tools:

Brush, roller or airless gun.

### Storage:

Store in tightly closed container for 24 months of the date of production in a cool and dry place.

### V.O.C. class :

A/i One – pack performance coatings (S.B). V.O.C. limit: 500 gr/lt. Maximum V.O.C. of product ready to use: 499 gr/lt. Maximum thinning: 10% v/v.



## FIELDS OF APPLICATION

Suitable for metal surfaces such as railings, agricultural machinery, chassis, etc, providing effective protection against corrosion, even under adverse weather conditions.

## SUBSTRATE PREPARATION

The surface must necessarily be sound, dry and free from dust, grease, or rust, to ensure good adhesion. Remove all loose or peeling old paint. Surfaces painted with oil paint of old, should be rubbed with sandpaper and dusted well.

## APPLICATION

Stir well the contents of the container before use, dilute and apply appropriate product care to cover well all the difficult parts of the surface, such as corners, recesses etc. Then close well the container to maintained in good condition for future use. It is stored in a tightly closed container for a long time. If you need a second hand, hover at least 12 hours after the first one.

## APPLICATION TEMPERATURE

Do not apply at temperatures lower than 5°C or before rain. Throughout application, the surface should not be exposed to direct sunlight. Adverse conditions during or shortly after application might alter the final properties of the product.

## TOOL CLEANING

Immediately after use, clean the brush, or roll with WHITE SPIRIT and then with hot water and detergent. Clean the gun with acetone, or NITRO SOLVENT UNIVERSAL LS-735. Do not empty washings into the groundwater.

## PRECAUTIONS

For information on the safe use, storage and disposal of the product read the information on the label and in the most recent Product Safety Data Sheet. The Product Safety Data Sheet is available at the professionals' request. Remaining paint should not be disposed of with household waste. You should seek advice from local authorities regarding the disposal and collection of waste.  
[Poisons Information Call Center 210 77.93.777](tel:2107793777)

Technical characteristics		Units	Standard	Value
Base				Alkyd resins
Density (20°C)		g/ml	EN ISO 2811.01-02	1.50 ± 0.05
Viscosity		sec	Flow Cup N°4	180 ± 30
Gloss(60°)			EN ISO 2813-99	< 15
Hardness (König) after 7 days		sec	ISO 1522-00	65 ± 15
Adhesion ( cross cut)			EN ISO 2409-95	0-1
Dilution with water	White spirit or turpentine for brush or roller	% v/v	-	5-7
	LS-703 solvent for gun application			7-10

\*Note: The measurements were taken in laboratory environment under a temperature of +23°C, Relative humidity 50% and without ventilation. It is possible for them to vary depending on the conditions prevailing at the worksite, such as temperature, humidity, ventilation, absorbability of the substrate.

The technical information and instructions contained in the present brochure and referring to the application and end use of Thrakon products are based on the up to now know-how and experience of the Company with regards to the products and are provided in good faith as long as such products are stored, used and applied as per Thrakon recommendations. Due to the inability, on our part, to directly inspect the conditions prevailing at the worksite as well as the application procedures of the product, the Company does not provide any guarantee with regards to the adequacy of its products for specific purpose while the Company shall not bear any legal responsibility based on the information stated in the present brochure or any other written, oral, or otherwise provided recommendations and instructions. The users of the products are advised to perform a limited surface testing of the products adequacy for the eventual application and use intentions. Thrakon reserves the right to modify the features of its products without prior notification. All orders shall be approved only following acceptance of the above and under the eventual Commercial Policy terms of the Company. The issuance of the present brochure voids any prior version.

Version B: 14/05/2025