

STATUS SUPREME

Premium quality ecological emulsion paint

STATUS SUPREME Eggshell Finish is a world-class stain-blocking ecological emulsion paint for use on all walls where an exceptional chic, luxury-looking, smooth, velvety and reflective finish with incomparable appearance. This innovative paint integrates the best technologies to deliver incomparable advantages in only one package. Ultimate Stain-Blocking Formula designed to stop toughest stains from penetrating into the paint film by cleaning hydrophilic and hydrophobic stains from beverages, edibles, markers, etc. The optimized Clean Guard formula gives outstanding resistance against household stains and It offers exceptional durability to frequent washing. Nanotech film delivers excellent surface protection. Supreme has been tested for toughest household stains, and is ideal for surfaces where outstanding durability is required. Advanced Color Block Technology formulated for exceptional richer and vibrant colors that stay looking fresh year after year delivering you long lasting beauty, in thousands of shades.



Advantages:

- Ultimate Stain- Blocking Formula.
- Color Block Technology
- Clean Guard Formula
- Outstanding resistance against household stains.
- Repeated washing with no color rub-off.
- Excellent surface protection.
- Excellent workability.
- Excellent coverage.
- Highly resistant to wear and aging.
- Suitable for use in kindergartens, children’s rooms, schools, hospitals.



TECHNICAL CHARACTERISTICS

Packaging:



Metallic containers
• 2.5 lt
• 5 lt

Color:



Available in white and in thousand of shades through STATUS tinting system.

Application:



For interior use.
Children’s bedroom, high traffic rooms, hallways, passages, healthcare, hospitality, hotels etc.

Consumption:



16-18 m²/lt



Drying time:

- Touch dry
1 - 2 h
Fully wash resistant after 7 days
- Recoating
2 - 3 h

*Drying times refer to normal ambient conditions (25°C, 60% humidity). Drying times may differ in case of ambient temperature and humidity variations.

Dilution with water:



5-10 (% v.v.)

Application tools:



Brush, roller, or airless gun.

Storage:



Store in tightly closed container in a cool and dry place at temperatures for 36 months of the date of production only if it has not been thinned.

V.O.C. class :



(a) Interior walls and ceilings (gloss < 25 at 60°) (W,B) V.O.C limit: 10 gr/lt
Minimum thinning with water: 10% v/v
Maximum V.O.C limit of ready to use product: 7.8 gr/lt

FIELDS OF APPLICATION

Suitable for busy homes and high traffic rooms, such as children's bedrooms, living rooms, dining rooms, kitchens, bathrooms, hallways and passages where cleaning is done often.

Suitable for healthcare, hospitality and educational environments and especially for hotels, hospitals, hospital corridors, schools and public building corridors.

SUBSTRATE PREPARATION

Before use, ensure that the surface is clean, dry, robust and free from dust, mold and grease. Remove damaged or peeling old paint. Where puttying is required, use the STATUS 100% ACRYLIC STUCCO and after drying, sand the surface down and dust well. If there are large cracks, use ready-to-use light white Stucco, STATUS ONE COVER, to fill the cracks applying just one coat without sanding. On new surfaces, first apply STATUS ELITE primer.

APPLICATION

Mix well before use, dilute properly and apply 1-2 coats of paint. Allow at least 2-3 hours before applying the second coat. Light colors cover the surface with two applications. Darker colors may require more layers for the achievement of an excellent result. In such cases we recommend coloring of the primer in a light hue of the same color, in order to facilitate coverage. Close the container tightly after use to keep the paint in good condition for future use. You can store undiluted paint in a tightly sealed container for extended periods of time without affecting the quality of the product. Allow 7 days before washing painted surfaces. They can be cleaned using a soft sponge with water and then wipe off.

APPLICATION TEMPERATURE

During the application temperatures should be at 5°-35°C and <80% RH. Do not start the application before rain. Ensure the surface is protected from direct solar radiation throughout the process. Adverse conditions during or immediately after application may affect the final properties of the product.

TOOL CLEANING

Immediately after use, drain excess paint thoroughly into the container and clean tools using warm soapy water. Do not dispose of washing waste water into the aquifer groundwater.

COMMENTS

More information regarding the reasons why this product was given the EU Ecolabel can be found on the EU website:

<http://ec.europa.eu/environment/ecolabel/>

PRECAUTIONS

For information on the safe use, storage and disposal of the product read the information on the label and in the most recent Product Safety Data Sheet. The Product Safety Data Sheet is available at the professionals' request. Remaining paint should not be disposed of with household waste. You should seek advice from local authorities regarding the disposal and collection of waste.

[Poisons Information Call Center 210 77.93.777](tel:2107793777)

Technical characteristics	Units	Standard	Value
Viscosity	cP	EN ISO 2555	10000 – 14000
Density	g/ml	EN ISO 2811-1	1.40 ± 0.03
- WHITE			1.35 ± 0.03
- BASE D			
pH		ISO 976	8.0 – 9.0
Gloss (60° C)	%	ISO 2813	≤5
Dilution	%	-	5 - 10
Recoating time	h		2 – 3
Drying time	h		1 - 2
Washing – scrubbing resistance		EN ISO 11998	Class 1

*Note: The measurements were taken in laboratory environment under a temperature of +23°C, Relative humidity 50% and without ventilation. It is possible for them to vary depending on the conditions prevailing at the worksite, such as temperature, humidity, ventilation, absorbability of the substrate.

The technical information and instructions contained in the present brochure and referring to the application and end use of Thrakon products are based on the up to now know-how and experience of the Company with regards to the products and are provided in good faith as long as such products are stored, used and applied as per Thrakon recommendations. Due to the inability, on our part, to directly inspect the conditions prevailing at the worksite as well as the application procedures of the product, the Company does not provide any guarantee with regards to the adequacy of its products for specific purpose while the Company shall not bear any legal responsibility based on the information stated in the present brochure or any other written, oral, or otherwise provided recommendations and instructions. The users of the products are advised to perform a limited surface testing of the products adequacy for the eventual application and use intentions. Thrakon reserves the right to modify the features of its products without prior notification. All orders shall be approved only following acceptance of the above and under the eventual Commercial Policy terms of the Company. The issuance of the present brochure voids any prior version.

Version B: 23/07/2024